



SAFETY DATA SHEET

CETOL WP 560

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name and/or code : CETOL WP 560

Manufacturer/Distributor : Akzo Nobel Industrial Coatings Ltd
 Unit 4a
 Mercer Way
 Shadsworth Business Park
 Blackburn
 Lancashire
 United Kingdom, BB1 2QZ
 Tel. Number: +44 (0) 1254 687950
 Fax Number: +44 (0) 1254 687960
 Internet: www.sikkens-joinery.com

e-mail address of person responsible for this SDS : industrial.msds@akzonobel.com

Product use : Waterborne coating for interior and exterior use.

Emergency telephone number (with hours of operation) : International Sikkens emergency number :
 Tel.: +31 71 3086944
 available 24 hours/day, every day of the week

2. HAZARDS IDENTIFICATION

The product is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification according to Regulation (EC) 1907/2006 (REACH)

Classification : Not classified.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC or assigned an occupational exposure limit.

Chemical name	CAS number	%	EC number	Classification
propane-1,2-diol	57-55-6	1 - 2.5	200-338-0	Not classified. [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

Workplace exposure limits, if available, are listed in section 8.

4. FIRST AID MEASURES

First-aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

5. FIRE-FIGHTING MEASURES

- Extinguishing media** : Recommended: alcohol-resistant foam, CO₂, powders, water spray.
- Extinguishing media not to be used** : Do not use water jet.
- Special exposure hazards** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

6. ACCIDENTAL RELEASE MEASURES

Due to the organic solvents content of the preparation:

- Personal precautions** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).
- Environmental precautions** : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.
- Methods for cleaning up** : Preferably clean with a detergent. Avoid using solvents.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

7. HANDLING AND STORAGE

- Handling** : Due to the organic solvents content of the preparation:
- Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.
- In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.
- Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.
- Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.
- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.
- Put on appropriate personal protective equipment (see section 8).
- Never use pressure to empty. Container is not a pressure vessel.
- Always keep in containers made from the same material as the original one.
- Comply with the health and safety at work laws.

7. HANDLING AND STORAGE

Storage : Store in accordance with local regulations. Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Due to the organic solvents content of the preparation:

Keep away from sources of ignition. Keep away from: oxidising agents, strong alkalis, strong acids.

No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<u>Ingredient name</u>	<u>Occupational exposure limits</u>
propane-1,2-diol	EH40/2005 WELs (United Kingdom (UK), 8/2007). TWA: 10 mg/m ³ 8 hour(s). Form: Particulate TWA: 150 ppm 8 hour(s). Form: Sum of vapour and particulates TWA: 474 mg/m ³ 8 hour(s). Form: Sum of vapour and particulates

Exposure controls : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Occupational exposure controls

Respiratory system : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

OLD LEAD-BASED PAINTS:

When surfaces are to be prepared for painting, account should be taken of the age of the property and the possibility that lead-pigmented paint might be present. There is a possibility that ingestion or inhalation of scrapings or dust arising from the preparation work could cause health effects. As a working rule you should assume that this will be the case if the age of the property is pre 1960.

Where possible wet sanding or chemical stripping methods should be used with surfaces of this type to avoid the creation of dust. When dry sanding cannot be avoided, and effective local exhaust ventilation is not available, it is recommended that a dust respirator is worn, that is approved for use with lead dusts, and its type selected on the basis of the COSHH assessment, taking into account the Workplace Exposure Limit for lead in air. Furthermore, steps should be taken to ensure containment of the dusts created, and that all practicable measures are taken to clean up thoroughly all deposits of dusts in and around the affected area.

The current Control of Lead at Work Regulations approved code of practice should be consulted for advice on protective clothing and personal hygiene precautions. Care should also be taken to exclude visitors, members of the household and especially children from the affected area, during the actual work and the subsequent clean up operations. All scrapings, dust, etc. should be disposed of by the professional painting contractor as Hazardous Waste.

Extra precautions will also need to be taken when burning off old lead-based paints because fumes containing lead will be produced. It is recommended that a respirator, approved for use with particulate fumes of lead is selected on the basis of the COSHH assessment, taking into account the Workplace Exposure Limit for lead in air. Similar precautions to those given above about sanding should be taken with reference to protective clothing, disposal of scrapings and dusts, and exclusion of other personnel and especially children from the building during actual work and the subsequent clean up operations.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Skin and body : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

Hands

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Eyes : Use safety eyewear designed to protect against splash of liquids.

Environmental exposure controls : Do not allow to enter drains or watercourses.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquid.

Flash point : Not applicable.

Viscosity : Kinematic: 2,44 cm²/s (244 cSt)

Relative density : 1,023

10. STABILITY AND REACTIVITY

Conditions to avoid : Stable under recommended storage and handling conditions (see section 7). When exposed to high temperatures may produce hazardous decomposition products.

Materials to avoid : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

Hazardous decomposition products : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

11. TOXICOLOGICAL INFORMATION

Toxicokinetics

Absorption : Not available.

Distribution : Not available.

Metabolism : Not available.

Elimination : Not available.

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Acute toxicity

Conclusion/Summary : Not available.

Chronic toxicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

Aquatic ecotoxicity

Conclusion/Summary : Not available.

Ecological information

Persistence/degradability

Conclusion/Summary : Not available.

PBT : Not applicable.

vPvB : Not applicable.

13. DISPOSAL CONSIDERATIONS

Do not allow to enter drains or watercourses.
Dispose of according to all federal, state and local applicable regulations.

Hazardous waste : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 91/689/EEC.

14. TRANSPORT INFORMATION

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

IMDG

Marine pollutant : No.

Special provisions : Not available.

ADR

Marine pollutant : No.

This product is not regulated for carriage according to ADR, IMDG.

15. REGULATORY INFORMATION

This product is not regulated for carriage according to ADR, IMDG. : The product is determined as not being dangerous according to the requirements of the DPD.

Risk phrases : This product is not classified according to EU legislation.

Safety phrases : S2- Keep out of the reach of children.
S24/25- Avoid contact with skin and eyes.
S29- Do not empty into drains.
S46- If swallowed, seek medical advice immediately and show this container or label.

Additional warning phrases (CEPE) : Not applicable.

The information in this Safety Data Sheet is required pursuant to Annex II to Regulation (EC) No 1907/2006.

16. OTHER INFORMATION

CEPE Classification : 2

Date of issue/Date of revision : 15-2-2011.

Version : 3

Notice to reader

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate

Date of issue/Date of revision : 15-2-2011.

Page: 5/6

16. OTHER INFORMATION

or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

Head Office

Akzo Nobel Decorative Coatings B.V, Rijksstraatweg 31, 2171 AJ Sassenheim, the Netherlands