stir before use | store and transport in a frost free area | store in a cool place | cleaning of equipment with water

WV 888

Product description	Defoamer to decrease foam building during application. Especially suitable for opaque white dipping and flow coating products.
Colour	Colorless
Packaging	5 L
Processing	For a better distribution of the defoamer it is recommended to pour the quantity of defoamer into a partial amount of the original material and mix before returning mixture into the complete amount and thoroughly stirring. Do not premix with water.
Consumption	addition quantity: 0,1-0,3%
Cleaning of equipment	Clean directly after use with water, if needed with washing up liquid or with ST 830.
Storage	The minimum storage stability of sealed containers is 2 years. Storage temperature: +5 - +30 °C. After ending of the storage time the product still can be usable, but some attributes may vary from new product. Therefore such over-stored product has to be applied with special attention. Opened cans must be sealed correctly! Store in a cool but frost-protected area.
Disposal	Only residue emptied cans can be disposed via recycling. Liquid wastes must be disposed of according to national regulations or according to EU-disposal key 08 01 12.
Hazard identification	In accordance with EC guide lines - Material safety data sheet, point 15.
Warning	Before use, read the identification and product information. Even when working with low emission products one should take care of the customary protection measures.
VOC guideline	Out of scope.
General instructions	For use in technical industrial companies and intended only for recommended Sikkens systems.

All details on our products contained in this publication do not represent details of the quality of the goods. The quality, suitability, qualification and function intended use of our goods shall be determined exclusively in accordance with the product descriptions based on the respective sales agreements. In each case, deviations typical of the sector shall be admissible, unless agreed in writing otherwise. All details correspond to todays state of technology. We make no claim as to the completness of the stated coating installations; they are stated merely as possible examples. Due to the large number of substrates and object conditions, the buyer/user shall not be released from his/her obligation to check our raw materials in a workmanlike manner for their suitability for the intended purpose on his/her own responsibility subject to the respective property conditions and process these in accordance with the respective state of technology. In other respects, our standard terms and conditions of sale apply. Upon the appearance of a new edition, this publication shall lose it's validity.

Akzo Nobel Industrial Coatings Ltd	Unit 4a, Mercer Way, Shadsworth Bus Pk	Blackburn, Lancs, BB12QZ	UNITED KINGDOM	Tel. +44 1254 687950	Fax. +44 1254 687960
Akzo Nobel Industrial Coatings Ltd	Unit 4a, Mercer Way, Shadsworth Bus Pk	Blackburn, Lancs, BB12QZ	Rep of IRELAND	Tel. +35 (0) 21 4220222	Fax. +35 (0) 21 4220205
Akzo Nobel Wood Coatings GmbH	Düsseldorfer Straße 96-100	D-40721 Hilden	GERMANY	Tel.: +49-2103-77-800	Fax: +49-2103-77-577