



for doors



store and transport
in a frost free area



polish

Pflegetuch

Product description Maintenance cloth for refreshing and protecting weathered painted surfaces of entry doors. Regular use extend the maintenance periods.

- water and dirt resistant
- good weather resistance
- good colour and gloss refresher

Colour Colorless

Packaging 1 Maintenance cloth (44 X 45 cm)

Processing The surface to be treated should first of all be cleaned thoroughly with the Special Cleaner* or suitable household cleaning agent and allowed to fully dry. After drying, the cleaned surface should be gently and evenly wiped using the maintenance cloth moistened with the balm. The cloth should be folded into a usable shape and the face of the cloth changed regularly during the application process.

Application temperature +5 - 30 °C for substrate, air and material at approx. 60 % R.H.

Drying times After the application, a drying time of approx. 30 min should be allowed.

Storage Minimum storage stability at room temperature: 2 years
Store cool but frost free.

Disposal The maintenance cloth can be disposed after use in the general waste disposal.

Hazard identification In accordance with EC guide lines - Material safety data sheet, point 15.

Warning Before use, read the identification and product information. Even when working with low emission products one should take care of the customary protection measures.

VOC guideline Out of scope.

General instructions Through the application of maintenance milk, painted surfaces obtain the original freshness. With regular use (1-2 yearly in spring and autumn), the durability of the coating system rises and maintenance periods can be extended. Defect coating systems cannot be repaired with maintenance milk. The correct products are referred to on the technical data sheets.

Relevant information Do not use on hot surfaces or direct sun radiation.

Before reworking of the maintained paint surface, the surface has to be cleaned with white spirit followed with a sanding (sanding paper K240). The clean and dry surface can be repainted with the Sikkens maintenance products.

All details on our products contained in this publication do not represent details of the quality of the goods. The quality, suitability, qualification and function intended use of our goods shall be determined exclusively in accordance with the product descriptions based on the respective sales agreements. In each case, deviations typical of the sector shall be admissible, unless agreed in writing otherwise. All details correspond to today's state of technology. We make no claim as to the completeness of the stated coating installations; they are stated merely as possible examples. Due to the large number of substrates and object conditions, the buyer/user shall not be released from his/her obligation to check our raw materials in a workmanlike manner for their suitability for the intended purpose on his/her own responsibility subject to the respective property conditions and process these in accordance with the respective state of technology. In other respects, our standard terms and conditions of sale apply. Upon the appearance of a new edition, this publication shall lose its validity.